



- Cable tie
- Natural, Nylon 6.6 material
- Black, Weather/UV resistant Nylon 6.6
- Halogen Free
- UL Recognized
- Flammability UL94 V-2
- Temperature, -40°C - 85°C

Solar Plus part number						
Nylon 6.6 Natural (Indoor Use)	Weather/UV Resistant Nylon 6.6 Black (Outdoor Use)	Lenght mm Panduit spec.	Width mm	Min. Loop Tensile Strength (Lbs.)	Std. Pkg. Qty.	Bulk Pkg. Qty.
5705150113710	5705150113727	100	2,5	18	100	
5705150113901	5705150113918	100	2,5	18		1000
5705150113734	5705150113741	142	2,5	18	100	
5705150113796	5705150113802	203	2,5	18	100	
5705150113758	5705150113765	142	3,6	40	100	
5705150113819	5705150113826	203	3,6	40	100	
5705150113772	5705150113789	188	4,8	50	100	
5705150113628	5705150113635	250	4,8	50	100	
5705150113642	5705150113659	300	4,8	50	100	
5705150113680	5705150113697	370	4,8	50	100	
5705150113666	5705150113673	368	7,6	120	50	
5705150113871	5705150113703	750	7,6	120	50	



- Allow cable tie entry from all four sides
- Low profile design keeps bundle close to mounting surface
- Black, Weather/UV resistant Nylon 6.6
- Natural, Nylon 6.6 material

Solar Plus part number					
Nylon 6.6 Natural (Indoor Use)	Weather/UV Resistant Nylon 6.6 Black (Outdoor Use)	Mounting Method	Lenght mm	Width mm Panduit spec.	Std. Pkg. Qty.
5705150113833	5705150113840	Rubber Adhesive	19	19	100
5705150113857	5705150113864	Rubber Adhesive	25	25	100
5705150113888	5705150113895	Screw mount	16	10,8	100